

ADVANTECH

快速漫游 高速通信


-业界最高效无线AP让网络随心所欲

赵国祥
工业通讯产品部中国区经理
研华科技


Open eAutomation, Boundless Integration

ADVANTECH
eAutomation


无线新技术开启新应用 (长距离)




无线新技术开启新应用 (监控)



无线新技术开启新应用 (高速移动)



无线新技术开启新应用 (小区监控)



研华全新无线产品介绍 (工业级室外无线AP)

One Radio
EKI-6321AG



Dual Radios
EKI-6322AG



Triple Radios
EKI-6323AG



强 固 室 外 设 计

- IP-67 rating housing
- Operation temp: -35 °C - 70 °C

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

研华全新无线产品介绍 (工业级室外无线AP)



Reversed Female N-type Connector

- 每一支天线都可以单独设定为802.11g(2.4GHz)或802.11a(5GHz)



强 固 室 外 设 计

- IP-67 rating housing
- Operation temp: -35 °C - 70 °C

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

研华全新无线产品介绍(工业级室外无线AP)



强 固 室 外 设 计

- IP-67 rating housing
- Operation temp: -35 °C - 70 °C

Waterproof M12 PoE port

Waterproof console port




Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

研华全新无线产品介绍(工业级室外无线AP)



Mounting Kit



PoE Injector

Data In

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

实际安装现场



Boundless Integration

ADVANTECH
eAutomation

EKI-6320AG系列

Features:

- IP-67 rating housing
- Operation temp: -35 °C - 70 °C
- Support PoE
- TCP/UDP Port and DSCP Level QoS
- Comprehensive Security Features :
WPA-PSK / WPA-EAP with TKIP/ CCMP WPA Encryption Type support
- 802.1x EAP-TLS / MD5 WEP Key support (Client and Server modes)
- Radius client
- MAC address filtering
- NAT
- Hide ESSID
- Multi-ESSID VLAN
- Firmware upgrade through TFTP, FTP
- SSH Telnet, Syslog, SNMP v1/v2
- CLI via console &Telnet, WebGUI

Open eAutomation, Boundless Integration



EKI-6320AG系列

重要特色:

- 长距离无线传输
“Daisy Chain Mesh” technology
- 多天线、智能无线传输
4 intelligent bandwidth management modes
- 高速无线漫游
Ultra fast roaming (< 10ms) over 140Km/h

Open eAutomation, Boundless Integration




Daisy Chain Mesh Technology

- 维持多跳后的高带宽
- 效能远超过市面上传统WDS模式
- 实测可达10~12Mbps @ 30Km



Daisy Chain




- 14 -

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation


Daisy Chain Mesh Technology

Dual Radio Application



High throughput
(12Mbps) maintained
after 5 distant hops!

Triple Radio Application




- 15 -

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

多天线、智能无线传输

- 支持 4 种智能传输模式：
无线带宽集成(端口汇聚)、无线备援、容错、负载均衡



高速无线漫游

- <10ms Handover between AP nodes
- Tx/Rx Path maintained by Daisy-Chain System



研华无线整体解决方案



Open eAutomation, Boundless Integration

ADVANTECH
eAutomation


研华无线整体解决方案



Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

研华无线整体解决方案



成功应用案例

成功应用案例(1)

- 长距离点对点无线传输
- 33.29Km from 苗栗 to 台中港, 台湾

Group/ Pair	Average (Mbps)	Minimum (Mbps)	Maximum (Mbps)
All Pairs	11.936	9.385	12.594
Pair 1	11.937	9.385	12.594
Totals:	11.936	9.385	12.594



Open eAutomation, Boundless Integration

ADVANTECH
eAutomation


成功应用案例(2)

- 无线热点: US Spring Campus



成功应用案例(3)

- 无线热点: Harbor & Mall, Florida, USA




- 24 -

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

成功应用案例(4)

- 无线热点:台北,台湾




- 25 -

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation


成功应用案例(5)

- 室外安全监控: Traffic Monitoring, Australia



成功应用案例(6)


- EMS (Environmental Monitoring System): 河川监控, 台湾



A1-A5 : 4 wireless hops in 5.7Km, total 8 cameras, 14~16Mbps bandwidth

成功应用案例(7)

- ITS(Intelligent Transportation System): 火车平交道监控, 台湾



Train Driver can watch the railway crossing status in 2-3km distance with the high speed mobility & roaming capability of EKI-6320 products


- 28 -

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

成功应用案例(8)

- 小区移动式监控:中国



A1-A10 : every 5km an AP, camera on police car, performance 10-12M bps

- 29 -

Open eAutomation, Boundless Integration

ADVANTECH
eAutomation

谢谢！



Open eAutomation, Boundless Integration

ADVANTECH
eAutomation